



TAYLOR® COMPANY

a Specialty Equipment company

Item No. _____

432

Frozen Beverage Freezer

Two Flavors

Features

Vary your menu by offering shakes & smoothies or frozen cocktails, fruit juices, coffees, cappuccino and tea slush beverages, all served at the desired thickness.

Freezing Cylinder

Two, 4 quart (3.8 liter).

Mix Hopper

Two, 12 quart (11.4 liter). Refrigerated to maintain mix below 41°F (5°C). Approved for dairy and non-dairy products.

Indicator Lights

Add Mix light alerts the operator to add mix. When the Mix Out light flashes, the unit automatically shuts down to prevent damage.

Automatic Consistency Control

A specially designed viscosity control automatically maintains superior product quality. An adjustable control allows the operator to serve a wide variety of frozen beverages at the desired thickness.

Lighted Display

Self-merchandising lighted display backlights the "Frozen Drink" flavor card and downlights the dispensing door.



Standard 6 & 18



SA2650



Selected 50 Hz. Models


Taylor Company has actively pursued all issues relating to the year 2000 to assure compliance. This includes all internal business systems, the entire equipment line manufactured by Taylor, and readiness of our suppliers.

Rockton, Illinois 61072
800-255-0626
Phone 815-624-8333 Fax 815-624-8000
www.taylor-company.com
e-mail: info@taylor-company.com

International Office
Taylor Company S.r.l.
Roma, Italy
Tel: +39-06-420-12002 Fax: +39-06-420-12034
e-mail: romeoff@taylor-company.com



432 Frozen Beverage Freezer



(Figures in parenthesis indicate centimeters)

Weights	lbs.	kgs.
Net	305	138.3
Crated	368	166.9
	cu. ft.	cu. m.
Volume	30.9	0.87

Dimensions	in.	mm.
Width	18-11/16	475
Depth	27-1/2	699
Height	36-5/8	929
Counter Clearance	---	---

Designed to rest on a plastic pad directly on counter top.

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Poles (P) Wires (W)
208-230/60/1 Air	20	17	2P 3W
208-230/60/3 Air	15	13	3P 4W
220-240/50/1 Air	15	13	2P 3W

This unit may be manufactured in other electrical characteristics. Refer to the local Taylor Distributor for availability. (For exact electrical information, always refer to the data label of the unit.)

Bidding Specs

Electrical: Volt _____ Hz _____ ph _____
 Neutral: Yes No Cooling: Air Water NA

Options: _____

Specifications

Electrical

One dedicated electrical connection is required. See the Electrical chart for the proper electrical requirements. Manufactured to be permanently connected. Consult your local Taylor distributor for cord & receptacle specifications as local codes allow.

Refrigeration System

One, approximately 6,000 BTU/hr compressor. R404A. (BTUs may vary depending on compressor used.)

Beater Motor

Two, 1/4 HP.

Air Cooled

Minimum Clearance: 6" (15.2 cm) on both sides. It is recommended to place the rear of the unit against the wall. Minimum air clearances must be met to assure adequate air flow for optimum performance.

Options

- Air Discharge Chute (Air Clearance 3" (7.6 cm) left side and rear. No clearance required on right side.
- Set of four Translight/Flavor Cards: Frozen Cappuccino, Frozen Cocktails, Shakes, Smoothies

Continuing research results in steady improvements; therefore, these specifications are subject to change without notice.